



Technical Data

3M™ Speed Stripper Concentrate 6A and 6H

Description

3M™ Speed Stripper Concentrate 6A is a concentrated product to be diluted and dispensed using only the 3M™ Flow Control System Wall Mount Dispenser or 3M™ Flow Control System Portable Dispenser.

3M™ Speed Stripper Concentrate 6H is a concentrated product to be diluted and dispensed using only the 3M™ Twist 'n Fill™ Cleaning Chemical Management System.

Ready-to-use Speed Stripper is formulated to quickly and effectively soften and remove floor finishes and sealers.

Special Features

- Automatic dispensing eliminates measuring and mixing and ensures accurate dilutions
- Excellent performance in removing multiple layers of finishes hardened from frequent burnishing
- Five-minute dwell time
- Low-foaming
- Mild fragrance
- Non-damaging to vinyl
- Non-ammoniated
- Low odor

Applications

Remove sealers, floor finish build-up and finishes from resilient floors.

Note: Do not use on wood floors, or floorings (such as linoleum) that may be affected by highly alkaline cleaners.

Packaging

Speed Stripper Concentrate 6A

- 0.5-gallon bottle
- 4 bottles per case

Each 0.5-gallon bottle yields 10 ready-to-use gallons.

Speed Stripper Concentrate 6H

- 0.528-gallon bottle
- 6 bottles per case

Each 0.528-gallon bottle yields 8.2 ready-to-use gallons.

General Use Directions

Refer to ready-to-use SDS for personal protective equipment (PPE) recommendations.

1. Dispense 3M™ Speed Stripper 6A using the 3M™ Flow Control System Dispenser or dispense 3M™ Speed Stripper 6H using the 3M™ Twist 'n Fill™ Cleaning Chemical Management System.
2. Sweep or dust mop the floor.
3. Properly locate caution signs for wet floor conditions.

4. Liberally apply diluted stripper solution to the floor with a mop, leaving the floor uniformly wet.
5. Allow stripper solution to remain wet on the floor for five to ten minutes.
6. Use a slow-speed floor machine (175 rpm) and a 3M 7200 Black Stripper Pad or 7300 High Productivity Pad to thoroughly strip the old finish off the floor.
7. Pick up dissolved finish, soil and stripper with a wet vacuum.
8. Flood-rinse the floor and pick up the rinse solution with a wet vacuum.
9. Mop the floor with clean water.
10. Let the floor dry completely before applying new finish.

Note: Floors become very slippery when stripper softens finish.

If more than 10 coats, contact 3M Rep for ideas on how to quickly remove.

NOTE:

Refer to product Safety Data Sheets or specific health hazard, first aid and precautionary information.

- 11-9287-1 (Concentrate)
- 11-9288-9 (RTU)

3M Branch Sales Offices

ANCHORAGE

11151 Calaska Circle
Anchorage, AK 99515

Telephone: 907/522-5200
Facsimile 907/522-1645

HONOLULU

4443 Malaai Street
Honolulu, HI 96818
Mail to: P.O. Box 30048
Honolulu, HI 96820

Telephone: 808/422-2721
Facsimile 808/422-9557

CONTINENTAL UNITED STATES

Customer Service Department
3M Center, Building 224-2S-04
St. Paul, MN 55144-1000

Order Entry/Status: 1-800-852-9722
Facsimile: 1-800-447-0408
CCD: bst@mmm.com

CANADA

1840 Oxford Street East
London, Ontario, Canada
N5V 3G2
Mail to: P.O. Box 5757
London, Ontario, Canada
N6A 4T1

Telephone: 800/364-3577
Facsimile: 800/479-4453

Important Notice to User

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty and Limited Remedy: 3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal or equitable theory asserted.



Commercial Solutions Division

St. Paul, MN 55144-1000
1-800-852-9722
www.3M.com/facility

3M and Twist'n Fill are trademarks of 3M Company.
Used under license in Canada.
© 3M 2015. All rights reserved.
Asset ID