

# MAXIM PLUS<sup>TM</sup>

LABEL SYSTEM

## Semi-Permanent Acrylic Floor Sealer

### Features:

**Seals & Finishes Most Porous Stone, Terrazzo,  
& Concrete Floors**  
**Extremely Durable & Economical**

### Description

This product is specially designed to seal and finish stone, terrazzo, and concrete floors. This product is compatible with all types of acrylic emulsion finishes. Special wetting agents allow for the penetration and sealing of microscopic pores and ridges of non-resilient floor surfaces.

### Directions

- 

**1** **Wear safety glasses & gloves**  
*Usar gafas de seguridad y guantes*
- 

**2** **Apply 1 - 2 coats evenly with clean mop**  
*Aplique uniformemente 1-2 capas con una mopa de limpia*
- 

**3** **Allow to dry 30 - 45 minutes between coats**  
*Deje secar 30-45 minutos entre una capa y otra*
- 

**4** **Completely dry before applying next coat**  
*Seque completamente antes de aplicar la capa siguiente*
- 

**5** **Apply floor finish**  
*Aplique el acabado para pisos*



### Applications

- For low maintenance areas such as:**
- > Schools and offices
  - > Hospitals and institutions
  - > Supermarkets and shopping centers

### Specifications

Color .....	White
Fragrance .....	Characteristic
pH Range .....	8.0 - 8.5
Dilution .....	RTU
Density .....	8.50
Non-volatile solids .....	16%
Coverage .....	2000 sq. ft. / gal.

### Packaging

4/1 gallon	115000-41
5 gallon	115000-05
2/2.5 gallon	115000-07
55 gallon	115000-55